

**BOARD OF FIRE COMMISSIONERS
WOODBIDGE TOWNSHIP DISTRICT # 9**

**ADDENDUM #1 TO RE-BID TO REFURBISH
SAULSBURY AIR LIGHT UNIT 9-3-4 FIRETRUCK**

Dated: January 13, 2023

CHASSIS CAB AND BODY PAINTING SPECIFICATIONS

The chassis cab shall be re-painted with the apparatus body, using a multi-step finishing system developed by the bidder and approved by the paint supplier. The final painting shall insure a durable, high gloss, finish to fire apparatus standards.

The interior compartments shall be re-sanded with a swirl DA finish equal to the present interior compartment surfaces. The exterior of the cab and body as well as any associated components shall be painted using the following procedure:

- The exterior surfaces shall be ground to provide a smooth surface which shall accept automotive body painting.
- The components are to be chemically cleaned on all surfaces.
- All surfaces shall be sanded to proper levels and all sanding residue removed.
- Any imperfections or defects discovered shall be filled with premium body filler and sanded smooth.
- A top-quality primer-filler shall be applied over the body, filled in required areas and sanded to eliminate all imperfections.
- The components shall be primed with the paint manufacturer's recommended primer.
- The entire primed surface shall be thoroughly sanded and the body surfaces shall be inspected for any imperfections and properly corrected.
- The apparatus cab and body shall be thoroughly cleaned with a wax and grease remover.
- The painting process shall be a base coat and clear coat then buffed following the guidelines as established by the paint manufacturer.

The cab and body shall be re-painted using a single color to match the cab primary color. Compartment doors shall be removed from the apparatus, hinges removed, and the doors re-painted. Interior of compartment doors shall have new rubber moldings and weatherstripping installed during reinstallation.

The chassis frame rails and underbody sheet metal shall be re-painted with a protective gloss black paint coating. The re-painting of the apparatus shall carry a minimum of five (5) year warranty against peeling or any other defects in workmanship or materials.